

Huebsch®

MULTI-HOUSING

Electronic Homestyle
Front Control
Washers and Dryers



BUILT FOR **RELIABLE** PERFORMANCE.

100 years. It's a long time for any company to be at the forefront of an industry. It's given us a long time to refine our craft, down to the smallest detail. For more than a century, Huebsch has built a legacy on providing proven premium quality laundry equipment that stands up to any challenge. We make no compromises in performance. We refuse to be outdone in reliability and efficiency. And our commitment to quality is matched only by our commitment to you.

The result is the most reliable machine in the industry. We believe that strength comes from within. That's why every technical feature and every component of a Huebsch machine is built specifically for the commercial environment. Our world-class test lab rigorously pushes our products far beyond the conditions they're likely to ever face. We work hard at every point of our manufacturing process to ensure that our machines reflect that belief. Huebsch front load laundry products have met every design standard to be 100% ADA compliant.

ELECTRONIC HOMESTYLE CONTROL

Electronic homestyle control is designed for durability and easy operation with attractive selection buttons and cycle status indicator lights.



FRONT LOAD WASHER

The Huebsch freestanding front load washer is constructed from the highest-quality materials. Ultra high efficiency saves energy and water.



FEATURES

REVOLUTIONARY BALANCING TECHNOLOGY

Improved out-of-balance technology that uses a redesigned suspension and advanced sensing to manage and redistribute out-of-balanced loads, delivering uninterrupted cycles.

LOW WATER USAGE

Per cycle to reduce operating costs.

HIGH SPEED EXTRACT

1200 RPM final spin exerts 440 G-Force to maximize moisture removal from clothes.

LARGER DOOR OPENING

Extra wide 15.5" (394 cm) for easy loading and unloading of clothes.

STAINLESS STEEL WASH TUB

Comes with a lifetime warranty, and actually becomes smoother with each use, so it won't pill, snag or fray clothes.

FOUR COMPARTMENT SUPPLY DISPENSER

Prewash, wash, fabric softener, bleach.



SINGLE LOAD DRYER

Huebsch's front control dryer, defined by its simplicity and its performance, provides everything you need to get the job done – and nothing you don't.

Huebsch's single load dryer combines heavy-duty construction with reliable operation proven to stand the test of time. Designed with less moving parts for one reason: so you'll face fewer maintenance problems and less wear and tear down the road. Our cabinet design maintains the perfect balance of heat, airflow and tumble action for optimal performance and efficiency.

FEATURES

SUPERIOR DRYING CONVENIENCE

With a 2.06 sq. ft. (1914 cm²) door opening, making it the widest in the industry, Huebsch dryers offer the convenience of easy loading and unloading.

EFFICIENT DRYER HEATING

With 25,000 BTU (gas models) and up to 5,350 Watts (electric models), Huebsch dryers offer some of the fastest drying times in the industry.

UPFRONT LINT FILTER

Easy to clean and secured.


REVERSIBLE DOOR (SOLID DOORS ONLY)

For installation flexibility.



STACK WASHER/DRYER

Huebsch's stack washer/dryer features brings an innovative stacked concept that takes up half the floor space that a conventional washer and dryer does when situated side by side. The freestanding softmount design can be installed on most floor types or levels. Both washer and dryer have the same hookups and connections as a standard washer and dryer. No additional plumbing or electrical change is needed. Same great features as the front control washer and dryer for superior washing and drying convenience. Washer is ADA compliant.



ELECTRONIC HOMESTYLE CONTROL COMMERCIAL WASHER & DRYER SPECIFICATIONS

MODELS	Front Load Washer	Single Load Dryer		Stack Washer/Dryer	
	YFNE5BJP113CW01	Electric 240: YDEE5BGS173CW01 Gas: YDGE5BGS113CW01		Electric 240: YTEE5ASP283CW01 Gas: YTGE5ASP093CW01	
Basket/Cylinder Volume liters (cu. ft.)	96.8 (3.42) stainless	198 (70) galvanized		96.8 (3.42) stainless 70 (198) galvanized	
Width - mm (in)	683 (26 7/8)	683 (26 7/8)		683 (26 7/8)	
Depth - mm (in)	704 (27 3/4)	711 (28)		704 (27 3/4)	
Height* - mm (in)	1027 (40 7/16)	1027 (40 7/16)		1986 (78 3/16)	
Weight - kg (lb)	113 (250)	Electric: 66 (145) Gas: 68 (150)		177 (390)	
Shipping Weight - kg (lb)	122 (270)	Electric: 68 (155) Gas: 73 (160)		193 (425)	
Cycle Time - minutes (default)	30-44	45		30-44	
Motor	0.9 HP 671 W	0.25 (1/3)		Washer: 0.9 HP 671 W Dryer: 1/3 HP, 5.5 amps	
Water Consumption - Liter (gal)	44.3 (11.7)	N/A		44.3 (11.7)	
Water Factor "WF" - Liters/Liter/cycle (gal/ft³)	0.5 (3.7)	N/A		0.5 (3.7)	
Modified Energy Factor "MEF" Liters/kWh/cycle (ft³/kWh/cycle)	82.29 (2.38)	N/A		82.29 (2.38)	
Average Hot Water Per Cycle Liter (ga)	1.4 (0.4)	N/A		1.4 (0.4)	
Water Pressure PSI (Bar) - 20-120	1.4-8.3	N/A		1.4-8.3	
Spin Speed - RPM	500, 800, 1200	N/A		500, 800, 1200	
Cycle/Temperature	Heavy Duty Normal Eco Perm Press Delicate Rinse & Spin Spin Only	Hot Warm Cold	Regular Delicate Perm Press Time Dry Quick Dry Fluff Up	Heavy Duty Normal Eco Perm Press Delicate Rinse & Spin Spin Only	Regular Perm Press Delicate Time Dry Quick Dry Fluff Up
Electrical Specifications and Circuit Requirements [ONE Power Cord for Both Units] +	120/60/1-15 amp	Electric: 208/60/1-30 amp Gas: 240/60/1-30 amp* 120-60/1-15 amp		Electric 240:+ 240/60/1 40 amp* Gas:+ 120/60/1 20 amp	
Btu per Hour (kcal)	N/A	22,500 (5,670)		25,000 (6300)	
Heating Element	N/A	4750W, 208V 5350W, 240V		4750W, 208V 5350W, 240V	
Type of Gas (Gas models only)	N/A	Factory-equipped natural/mixed gas convertible to LP gas**		Factory-equipped natural/mixed gas convertible to LP gas**	
Utility Connections - mm (in)	N/A	Gas: 3/8" NPT (9.5)		Gas: 3/8" NPT (9.5)	
Air Outlet Diameter - mm (in)	N/A	102 (4)		102 (4)	
Exhaust Airflow - cfm (liters/sec) †	N/A	105 (220)		105 (220)	
Maximum Exhaust Static Back Pressure	N/A	0.6" W.C.		0.6" W.C.	
Agency Approval	cCSAus	Electric: cULus Gas: cCSAus		Electric: cULus Gas: cCSAus	
Activation	Electronic	Electronic		Electronic	
Top and Lid Finish	Porcelain	Porcelain		N/A	
Colors	White	White		White	
Door Type	Window	Solid		Window	
Supply Injection	Yes	N/A		No	

* Electric dryers come equipped for 240/60/1 operation. They can be field converted to operate on 208/60/1 with optional 61928 conversion kit. Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

** IMPORTANT: Any product revisions or conversions must be made by the Manufacturer's Authorized Dealers, Distributors, or local service personnel.

† Measured at point of exit from dryer.

+ ONE Power Cord for Both Units

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008. Printed in the U.S.A.

Huebsch®