

Huebsch®

MULTI-HOUSING

Electronic Homestyle
Rear Control
Washers and Dryers



BUILT FOR **RELIABLE** PERFORMANCE.

100 years. It's a long time for any company to be at the forefront of an industry. It's given us a long time to refine our craft, down to the smallest detail. For more than a century, Huebsch has built a legacy on providing proven premium quality laundry equipment that stands up to any challenge. We make no compromises in performance. We refuse to be outdone in reliability and efficiency. And our commitment to quality is matched only by our commitment to you.

The result is the most reliable machine in the industry. We believe that strength comes from within. That's why every technical feature and every component of a Huebsch machine is built specifically for the commercial environment. Our world-class test lab rigorously pushes our products far beyond the conditions they're likely to ever face. We work hard at every point of our manufacturing process to ensure that our machines reflect that belief.

ELECTRONIC HOMESTYLE CONTROL

Electronic homestyle control is designed for durability and easy operation with attractive selection buttons and cycle status indicator lights.



Huebsch®



TOP LOAD WASHER

The Huebsch freestanding front load washer is constructed from the highest-quality materials. Ultra high efficiency saves energy and water.

FEATURES

HIGH SPEED EXTRACT

710 RPM final spin to maximize moisture removal from clothes.

AUTOMATIC BALANCING SUSPENSION SYSTEM

Rear self-leveling legs maximize smooth and quiet operation on all floor types.

DURABLE STAINLESS STEEL WASH TUB

Comes with a lifetime warranty, and actually becomes smoother with each use, so it won't pill, snag or fray clothes.

POLYTUFF® CURVED FOUR-VANE POLYPROPYLENE AGITATOR

High vanes and extra long 210° agitation stroke delivers superior washability for all load sizes.



FRONT LOAD WASHER

The Huebsch freestanding front load washer is constructed from the highest-quality materials. Ultra high efficiency saves energy and water.

FEATURES

REVOLUTIONARY BALANCING TECHNOLOGY

Improved out-of-balance technology that uses a redesigned suspension and advanced sensing to manage and redistribute out-of-balanced loads, delivering uninterrupted cycles.

HIGH SPEED EXTRACT

1200 RPM final spin exerts 440 G-Force to maximize moisture removal from clothes.

STAINLESS STEEL WASH TUB

Comes with a lifetime warranty, and actually becomes smoother with each use, so it won't pill, snag or fray clothes.



LARGER DOOR OPENING

Extra wide 15.5" (394 cm) for easy loading and unloading of clothes.

LOW WATER USAGE

Per cycle to reduce operating costs.

FOUR COMPARTMENT SUPPLY DISPENSER

Prewash, wash, fabric softener, bleach.



ENERGY STAR®
Certified

SINGLE LOAD DRYER

Huebsch's front control dryer, defined by its simplicity and its performance, provides everything you need to get the job done – and nothing you don't.

Huebsch's single load dryer combines heavy-duty construction with reliable operation proven to stand the test of time. Designed with less moving parts for one reason: so you'll face fewer maintenance problems and less wear and tear down the road. Our cabinet design maintains the perfect balance of heat, airflow and tumble action for optimal performance and efficiency.

FEATURES

SUPERIOR DRYING CONVENIENCE

With a 2.06 sq. ft. (1914 cm²) door opening, making it the widest in the industry, Huebsch dryers offer the convenience of easy loading and unloading.

EFFICIENT DRYER HEATING

With 25,000 BTU (gas models) and up to 5,350 Watts (electric models), Huebsch dryers offer some of the fastest drying times in the industry.

UPFRONT LINT FILTER

Easy to clean and secured.

REVERSIBLE DOOR (SOLID DOORS ONLY)

For installation flexibility.



ELECTRONIC HOMESTYLE CONTROL COMMERCIAL WASHER & DRYER SPECIFICATIONS

MODELS	Top Load Washer	Front Load Washer	Single Load Dryer	
	YWNE52PP113CW01	YFNE5RSP113CW01	Electric 208: Electric 240: Gas:	YDEE7RGS153CW01 YDEE7RGS173CW01 YDGE7RGS113CW01
Basket/Cylinder Volume liters (cu. ft.)	3.26 (92.3) blue porcelain	96.8 (3.42) stainless	198 (7.0) galvanized	
Width - mm (in)	650 (25 5/8)	683 (26 7/8)	683 (26 7/8)	
Depth - mm (in)	711 (28)	704 (27 3/4)	711 (28)	
Height - mm (in)	1092 (43)	1092 (43)	1092 (43)	
Weight - kg (lb)	82 (180)	109 (240)	Electric: Gas:	59 (130) 61 (135)
Shipping Weight - kg (lb)	88 (195)	118 (260)	Electric: Gas::	64 (140) 66 (145)
Cycle Time - minutes (default)	30-44	30-44	45	
Motor - HP (kW)	0.37 (1/2)	0.9 (671)	0.25 (1/3)	
Water Consumption - Liter (gal)	92.2 (24.3)	44.3 (11.7)	N/A	
Water Factor "WF" Liters/Liter/cycle (gal/ft³)	53.36 (1.29)	0.50 (3.7)	N/A	
Modified Energy Factor "MEF" Liters/kWh/cycle (ft³/kWh/cycle)	1.12 (8.4)	82.29 (2.38)	N/A	
Average Hot Water Per Cycle Liter (gal)	7.0 (1.9)	1.4 (0.4)	N/A	
Water Pressure PSI (Bar) - 20-120	1.4-8.3	1.4-8.3	N/A	
Spin Speed G-Force (RPM)	150 (710)	500, 800, 1200	N/A	
Cycle/Temperature	Heavy Duty Normal Eco Perm Press Delicate Rinse & Spin Spin Only	Hot Warm Cold	Heavy Duty Normal Eco Perm Press Delicate Rinse & Spin Spin	Hot Warm Cold
Regular Perm Press Delicate				No Heat Low High
Electrical Specifications and Circuit Requirements [ONE Power Cord for Both Units] +	120/60/1-15 amp	120/60/1-15 amp	Electric:+ Gas:+	208/60/1-30 amp 240/60/1-30 amp* 120-60/1-15 amp
Btu per Hour (kcal)	N/A	N/A	22, 500 (5,670)	
Heating Element	N/A	N/A	4750W, 208V 5350W, 240V	
Type of Gas (Gas models only)	N/A	N/A	Factory-equipped natural/mixed gas convertible to LP gas**	
Utility Connections - mm (in)	N/A	N/A	Gas: 3/8" NPT (9.5)	
Air Outlet Diameter - mm (in)	N/A	N/A	102 (4)	
Exhaust Airflow - cfm (liters/sec) †	N/A	N/A	105 (220)	
Maximum Exhaust Static Back Pressure	N/A	N/A	0.6" W.C.	
Agency Approval	cCSAus	cCSAus	Electric: Gas:	UL _{us} cCSAus
Activation	Electronic	Electronic	Electronic	
Top and Lid Finish	Porcelain	Porcelain	Porcelain	
Colors	White	White	White	

* Electric dryers come equipped for 240/60/1 operation. They can be field converted to operate on 208/60/1 with optional 61928 conversion kit. Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

** IMPORTANT: Any product revisions or conversions must be made by the Manufacturer's Authorized Dealers, Distributors, or local service personnel.

† Measured at point of exit from dryer.

+ ONE Power Cord for Both Units

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008. Printed in the U.S.A.

Huebsch®