

Huebsch®

MULTI-HOUSING

Quantum® Front Control
Commercial Washers & Dryers

COIN
CARD VEND



BUILT FOR **RELIABLE** PERFORMANCE.

Huebsch's commitment to multi-housing laundry is unmatched anywhere else in the industry. Built for performance and reliability, our laundry machines maximize your profitability and provide unparalleled convenience for your property.

Huebsch's line of washers and dryers are ready to meet the demands of your laundry room. They are designed to work as a single or stacked laundry setup, provide maximum energy efficiency and long-lasting performance. Huebsch front load laundry products have met every design standard to be 100% ADA compliant.

EQUIPPED WITH QUANTUM CONTROLS TO PROVIDE:

Total automated management of your laundry room. Its simple, powerful programming gives you the ability to:

- Easily manage your laundry operation with remote internet access.
- Establish multi-level vend prices, soil level cycles and dryer top-off times on your machines.
- Track coin or card transactions.
- WashAlert™ with Service Alert capable.



ACTIVATION TYPES

Offering a variety of activation types allowing you to tailor your laundry room to fit your needs. Front control models all come with high capacity meter case.



Coin ("C")



Prep for Card ("Y")



Prep for Coin ("X")

FRONT LOAD WASHER



The Huebsch front load washer gives building owners and property managers unparalleled ability to reduce water and energy costs through advanced programmability.

FEATURES

REVOLUTIONARY BALANCING TECHNOLOGY

Improved out-of-balance technology that uses a redesigned suspension and advanced sensing to manage and redistribute out-of-balanced loads, delivering uninterrupted cycles.

LOW WATER USAGE

Per cycle to reduce operating costs.

HIGH SPEED EXTRACT

1200 RPM final spin exerts 440 G-Force to maximize moisture removal from clothes.

LARGER DOOR OPENING

Extra wide 15.5" (394 cm) for easy loading and unloading of clothes.

STAINLESS STEEL WASH TUB

Comes with a lifetime warranty, and actually becomes smoother with each use, so it won't pill, snag or fray clothes.

FOUR COMPARTMENT SUPPLY DISPENSER

Prewash, wash, fabric softener, bleach.



SINGLE LOAD DRYER



Huebsch's front control dryer, defined by its simplicity and its performance, provides everything you need to get the job done – and nothing you don't. Huebsch's single load dryers combine heavy-duty construction with reliable operation proven to stand the test of time. They're designed with less moving parts for one reason: so you'll face fewer maintenance problems and less wear and tear down the road. The perfect balance of heat, airflow and tumble action for optimal performance and efficiency.

FEATURES

SUPERIOR DRYING CONVENIENCE

With a 2.06 sq. ft. (1914 cm²) door opening, making it the widest in the industry, Huebsch dryers offer the convenience of easy loading and unloading.

UPFRONT LINT FILTER

Easy to clean and secured.

REVERSIBLE DOOR (SOLID DOORS ONLY)

For installation flexibility.

EFFICIENT DRYER HEATING

25,000 BTU (gas models) and 5,350 Watts (electric models) provide fast drying and lower operating costs.



STACK DRYER


The Huebsch stack dryer offers the same great features as the single load dryer. Two commercial dryers in the space of one, both operating independently, including independent controls for optimum usage. Bottom dryer is ADA Compliant.



STACK WASHER/DRYER



Huebsch's stack washer/dryer bring an innovative stacked concept that takes up half the floor space that a conventional washer and dryer does when situated side by side. The freestanding softmount design can be installed on all floor types or levels. Both washer and dryer have the same hookups and connections as a standard washer and dryer. No additional plumbing or electrical change is needed. Same great features as the front control washer and dryer for superior washing and drying convenience. Washer is ADA Compliant.



MODELS and ACTIVATION (NOTE: Coin Box Sold Separately)	Front Load Washer	Single Load Dryer	Stack Dryer	Stack Washer/Dryer
COIN	HFNNEASP113CW01	Electric 208: HDENEAGS153CW01 Electric 240: HDENEAGS173CW01 Gas: HDGNEAGS113CW01		
PREP CARD	HFNNYASP113CW01	Electric 208: HDENYAGS153CW01 Electric 240: HDENYAGS173CW01 Gas: HDGNYAGS113CW01	Electric 208: HSENYAGW293CW01 Electric 240: HSENYAGW283CW01 Gas: HSGNYAGW093CW01	Electric 208: HTENYASP293CW01 Electric 240: HTENYASP283CW01
PREP COIN	HFNNXASP113CW01		Electric 208: HSENXAGW293CW01 Electric 240: HSENXAGW283CW01 Gas: HSGNXAGW093CW01	Electric 208: HTENXASP293CW01 Electric 240: HTENXASP283CW01 Gas: HTGNXASP093CW01
Stainless Basket/Cylinder Volume - cu.ft. (liters)	96.8 (3.42)	198 (70)	198 (70) ea pocket	96.8 (3.42) 198 (70)
Width - mm (in)	683 (26 7/8)	683 (26 7/8)	683 (26 7/8)	683 (26 7/8)
Depth - mm (in)	704 (27 3/4)	28 (711)	28 (711)	27 3/4 (704)
Height* - mm (in)	1126 (44 3/8)	1126 (44 3/8)	1986 (78 3/16)	1986 (78 3/16)
Weight - kg (lb)	122.5 (270)	Electric: 68 (150) Gas: 70 (155)	Electric: 120 (265) Gas: 125 (275)	Electric: 177 (390)
Shipping Weight - kg (lb)	131.5 (290)	Electric: 73 (160) Gas: 75 (165)	Electric: 127 (280) Gas: 132 (290)	Electric: 193 (425)
Cycle Time - minutes (default)	27	45	45	27/45
Motor HP (Capacitor Start and Thermal Protected)	0.9 HP 671 W	1/3 HP, 5.5 amps	1/3 HP, 5.5 amps	0.9 HP 671 W 1/3 HP, 5.5 amps
Water Consumption - Liter (gal)	44.3 (11.7)	N/A	N/A	44.3 (11.7)
Water Factor "WF" Liters/Liter/cycle (gal/ft³)	0.52 (3.8)	N/A	N/A	0.52 (3.8)
Modified Energy Factor "MEF" Liters/kWh/cycle (ft³/kWh/cycle)	84.48 (2.98)	N/A	N/A	84.48 (2.98)
Average Hot Water Usage - Liter (gal)	1.5 (0.4)	N/A	N/A	1.5 (0.4)
Water Pressure PSI (Bar)	20-120 (1.4-8.3)	N/A	N/A	20-120 (1.4-8.3)
Spin Speed - RPM	500, 800, 1200	N/A	N/A	500, 800, 1200
Cycle/Temperature	Hot Normal Warm Perm Press Cold Delicate	High 160 ° Medium 155 ° Low 145 ° Delicate 115 ° No Heat	High 160 ° Medium 155 ° Low 145 ° Delicate 115 ° No Heat	Hot Normal Warm Perm Press Cold Delicate High 160 ° Medium 155 ° Low 145 ° Delicate 115 ° No Heat
Electrical Specifications and Circuit Requirements [ONE Power Cord for Both Units]+	120/60/1-15 amp	Electric: 208/60/1-30 amp 240/60/1-30 amp* Gas: 120/60/1-15 amp	Electric: 2 ea 208/60/1-30 amp 240/60/1-30 amp* Gas: 2 ea 120/60/1-15 amp	Electric:+ 208/60/1-30 amp 240/60/1-30 amp* Gas:+ 120/60/1-15 amp
Btu per Hour (kcal)	N/A	25,000 (6300)	25,000 (6300)	25,000 (6300)
Heating Element	N/A	4750W, 208V 5350W, 240V	4750W, 208V 5350W, 240V	4750W, 208V 5350W, 240V
Type of Gas (Gas models only)	N/A	Factory-equipped natural/mixed gas convertible to LP gas**	Factory-equipped natural/mixed gas convertible to LP gas**	Factory-equipped natural/mixed gas convertible to LP gas**
Utility Connections - mm (in)	N/A	Gas: 3/8 NPT (9.5)	Gas: 3/8 NPT (9.5)	Gas: 3/8" NPT (9.5)
Air Outlet Diameter - mm (in)	N/A	102 (4)	102 (4)	102 (4)
Exhaust Airflow - cfm (liters/sec) †	N/A	105 (220)	105 (220)	105 (220)
Maximum Exhaust Static Back Pressure	N/A	0.6" W.C.	0.6" W.C.	0.6" W.C.
Agency Approval	cCSAus	Electric: cULus Gas: cCSAus	Electric: cULus Gas: cCSAus	Electric: cULus Gas: cCSAus
Activation	Coin/Card Op	Coin/Card Op	Coin/Card Op	Coin/Card Op
Top and Lid Finish	Porcelain	Porcelain	N/A	N/A
Colors	White	White	White	White
Door Type	Window	Solid	Window	Window
Supply Injection	Available	N/A	N/A	N/A
Drain	Pump	N/A	N/A	Pump

* Electric dryers come equipped for 240/60/1 operation. They can be field converted to operate on 208/60/1 with optional 61928 conversion kit. Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

** IMPORTANT: Any product revisions or conversions must be made by the Manufacturer's Authorized Dealers, Distributors, or local service personnel.

† Measured at point of exit from dryer.

+ ONE Power Cord for Both Units

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008. Printed in the U.S.A.

