

DEDICATED TO A HIGHER STANDARD.

100 years. It's a long time for any company to be at the forefront of an industry. And you'd think that a company that's been able to lead for that long must have a finely honed craft — a premier product. Well, you'd be right. For more than a century, Speed Queen has built a legacy on providing equipment that stands up to any commercial laundry challenge. We make no compromises in performance. We refuse to be outdone in reliability and efficiency. Our commitment to quality is only matched by our commitment to your success. The result? The most profitable machines in the industry — bar none.

Some of our competitors may think that a residential machine wrapped in a rugged exterior passes for commercial grade. We believe that strength comes from within. Speed Queen machines are built specifically for the commercial environment. We use metal where others use plastic. Our world-class Test Lab rigorously pushes our products far beyond the conditions they'll face in the field. We believe in being there when our customers need us most. And we go the extra mile at every point of our manufacturing process to ensure that our machines reflect that belief.











CONTROL OPTIONS

QUANTUM® GOLD

Revolutionary Quantum® Gold technology combines equipment controls, programming and wireless networking into one full-store management system, including: wireless networking, adjustable water levels, "lucky cycle" feature, time of day pricing, customizable cycle modifiers, and in-depth reporting. Designed to reduce costs and maximize revenue, Quantum gives you the power to achieve unprecedented levels of profitability.

MICRO-DISPLAY CONTROL (MDC)

Our Micro-Display control clearly displays the vend price and keeps customers informed throughout the wash process with cycle status lights and a digital cycle countdown. Interfacing with a variety of aftermarket card reader systems, MDC offers four cycle selections, basic audit features and is available with a single coin drop installed.

E-MECH

The E-Mech control features a straightforward design that offers customers simple water temperature and fabric selections, using cue lights to monitor progress through the wash cycle. This control is designed to function with any coin slide manufacturer's equipment.

BUILT FOR RELIABLE PERFORMANCE.



FRONT LOAD WASHER

Revolutionary balancing technology redistributes even the most unbalanced loads for consistent cycle times, minimized vibration and reduced noise

Increase spin speed extracts 440 G-Force to maximize moisture removal, helping to minimize dry times.

20% increase in capacity with improved water usage for superior washability, increased customer satisfaction and lower utility bills.

Heavy-duty design features like a rugged suspension system and stainless steel washtub and outer drain tub to deliver long-lasting performance.

Redesigned 4-compartment soap dispenser for simplified use and cleaning with for time for flushing

TOP LOAD WASHER

Durable stainless steel tub becomes smoother with each use, so it won't pill, snag or fray clothes

710 RPM final spin speed extracts more water from loads reducing the energy costs associated with long drying times.

Advanced suspension system eliminates the possibility of an unbalanced load issue

Secure high-capacity coin vaults feature a double-wrapped steel front and are secured to the washer top with heavy duty bolts





SINGLE AND STACK DRYER

Extra-large capacity with the largest door opening in the industry for easy loading and unloading

Durable galvanized steel cylinder

Upfront lint filter for easy cleaning

Stack unit offers two dryers in floor space of one

MODELS	Front Load Washer	Front Load Washer	Top Load Washer	Top Load Washer - Short Tub	Single Dryer	Single Dryer	Stack Dryer/Dryer	Stack Washer/ Dryer	
Available Controls	Quantum, MDC	Quantum, MDC, E-Mech	Quantum, MDC, E-Mech	Quantum	Quantum, MDC	Quantum, MDC, E-Mech	Quantum, MDC, E-Mech	Quantum, MDC	
Available Control Location	Front	Rear	Rear	Rear	Front	Rear	Front	Front	
Capacity - Ib (kg)	21.5 (9.5)	21.5 (9.5)	16 (7.3)	14 (6.4)	18 (8.2)	18 (8.2)	18 (8.2)	See front control front load washer and dryer specs to left	
Cylinder Volume - cu. Ft. (liters)	3.42 (96.8)	3.42 (96.8)	3.26 (92.3)	2.9 (82)	7.0 (198)	7.0 (198)	7.0 (198)		
Width - in (mm)	26 7/8 (683)	26 7/8 (683)	25 5/8 (650)	25 5/8 (650)	26 7/8 (683)	26 7/8 (683)	26 7/8 (683)	26 7/8 (683)	
Depth - in (mm)	27 3/4 (704)	27 3/4 (704)	28 (711)	28 (711)	28 (711)	28 (711)	29 (737)	27 3/4 (704)	
Height - in (mm)	44 3/8 (1126)	43 (1092)	43 (1092)	43 (1092)	44 3/8 (1126)	43 (1092)	78 3/16 (1986)	78 3/16 (1986)	
Spin Speed G-Force (RPM)	440 (1200)	440 (1200)	150 (710)	150 (710)	N/A	N/A	N/A		
Motor Size - HP (kw)	Variable Speed Inc	duction 0.9 (0.67)	1/2 (0.37)	1/2 (0.37)	1/3 (0.25)	1/3 (0.25)	1/3 (0.25)		
Water Consumption per Cycle - g (I)*	11.7 (44.3)	11.7 (44.3)	24.6 (93)	16.6 (62.9)	N/A	N/A	N/A	See front control front load washer and dryer specs to left	
WF (Water Factor)	3.8	3.8	1.69	1.7	N/A	N/A	N/A		
MEF (Modified Energy Factor)	2.98	2.98	7.9	6.18	N/A	N/A	N/A		
Available Heat Sources	N/A	N/A	N/A	N/A	Gas or Electric	Gas or Electric	Gas or Electric		
Available Heating Element (Electric W)	N/A	N/A	N/A	N/A	5350 @ 240V	5350 @ 240V	5350 @ 240V		
Gas Inlet Connection - in (mm)	N/A	N/A	N/A	N/A	3/8 (9.5)	3/8 (9.5)	3/8 (9.5)		
Gas Consumption - BTU/Hr	N/A	N/A	N/A	N/A	25,000	25,000	25,000		
Exhaust Outlet Dia in (mm)	N/A	N/A	N/A	N/A	4 (102)	4 (102)	4 (102)		
Exhaust Airflow - cfm (liters/sec)	N/A	N/A	N/A	N/A	220 (105)	220 (105)	220 (105)		
Available Water Temperatures	3	3	3	3	N/A	N/A	N/A		
Available Cycles*	Normal, Perm Press, Delicate				High, Medium, Low, Delicates, No Heat				
Water Pressure - PSI (Bar)	20-120 (1.4/8.3)	20-120 (1.4/8.3)	20-120 (1.4/8.3)	20-120 (1.4/8.3)	N/A	N/A	N/A		
Cycle Indicator Lights	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Cylinder Finish	Stainless Steel	Stainless Steel	Stainless Steel, Porcelain	Stainless Steel, Porcelain	Galvanized	Galvanized	Galvanized		
Available Colors	White, Stainless	White	White	White	White, Stainless	White	White, Stainless	White	
Door Type (Solid/Window)	Window	Window	N/A	N/A	Solid	Solid	Solid or Window	Window	
Available Electrical Requirements - (Voltage/Hz/Ph - Circuit Amperage)	120/60/1 - 15 Amp	120/60/1 - 15 Amp	120/60/1 - 15 Amp	120/60/1 - 15 Amp	Gas: 120/60/1 - 15 Amp, Electric: 120/240/60/1 - 30 Amp			See front control front load washer and dryer specs to left	
Net Weight - Ib (kg)	270 (122)	253 (115)	190 (86)	190 (86)	Electric/Gas 150/155 (68/70)	Electric/Gas 135/140 (61/64)	Electric/Gas 265/275 (120/125)	390 (177)	
Shipping Weight - Ib (kg)	290 (132)	273 (124)	210 (95)	210 (95)	Electric/Gas 160/165 (73/75)	Electric/Gas 145/150 (66/68)	Electric/Gas 280/290 (127/132)	425 (193)	
Shipping Width - in (mm)	29 (737)	29 (737)	27 1/2 (699)	27 1/2 (699)	29 (737)	29 (737)	29 (737)	29 (737)	
Shipping Depth - in (mm)	32 3/4 (832)	32 3/4 (832)	30 (762)	30 (762)	32 3/4 (832)	32 3/4 (832)	32 3/4 (832)	32 3/4 (832)	
Shipping Height - in (mm)	45 1/2 (1156)	45 1/2 (1156)	44 1/4 (1124)	44 1/4 (1124)	45 1/2 (1156)	45 1/2 (1156)	80 (2032)	80 (2032)	
Available Agency Approvals	cULus	cULus	cULus	cULus	Electric: cULus, Gas: cCSAus	Electric: cULus, Gas: cCSAus	Electric: cULus, Gas: cCSAus	Electric: cULus, Gas: cCSAus	

ADA Compliant
Note: Not all options are available for all models. Refer to the price list for the available models and options.
*Information shown applies to highest end control available.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008. Printed in the USA.

speedqueencommercial.com

