

ON-PREMISES SOFT MOUNT WASHER-EXTRACTOR

180, 230 and 275lb



FEATURES

- Freestanding, high spin, 350 G-Force
- Stainless steel front and side panels
- Stainless steel cylinder and tub
- XControl+ – fully programmable control
- Up Front 5 Cup Soap Hopper
- Large dual drain valves
- Large door opening for easy loading and unloading
- SuperWash® perforated lifting ribs create more mechanical action
- SuperEco washing programs significantly reduce water and electricity consumption
- 10 Year Warranty: frame, outer tub, cylinder shaft assembly, bearing housing, cylinder bearings and bearing seals

OPTIONS

- Steam heating

3 YEAR PARTS
WARRANTY



ROBUST DESIGN



EXTRA LARGE
DOOR



LARGE DRAIN VALVE

TYPE		PY180	PY230	PY275	
INNER CYLINDER					
max capacity	lbs	180	230	275	
volume	cu ft	28.5	35.4	41.7	
diameter	in	43 11/16	47 1/4	51 3/16	
depth	in	33	33 7/8	34 1/4	
CYLINDER SPEED					
wash	rpm	36	33	32	
extraction	rpm	750	720	695	
G-FORCE					
Motor size	hp	14.75	20.12	24.81	
VOLTAGE					
	208-240/60/3	FLA/circuit breaker	30.2/40	35/50	37.8/50
	400-480/60/3	FLA/circuit breaker	23.8/30	25.2/40	29.4/40
DOOR					
opening size	in	20 7/8	20 7/8	25 5/8	
bottom to floor	in	40 1/8	43 1/8	42 1/2	
Water inlet connection	in	3 x 1 1/2	3 x 1 1/2	3 x 1 1/2	
Steam inlet connection	in	1	1	1	
Drain connection	in	2 x 4	2 x 4	2 x 4	
DIMENSIONS W/O TILT					
height	in	78 1/8	81 1/8	82 1/8	
width	in	58 7/8	70 1/2	73	
depth	in	76 3/8	78 15/16	82 1/8	
net weight	lbs	5820	6989	7672	
DIMENSIONS W/ TILT					
height	in	97 1/2	101 3/8	103 1/2	
width	in	61 5/8	72 7/8	74 9/16	
depth	in	93 11/16	99 3/4	100 1/2	
net weight	lbs	6592	7760	8466	
SHIPPING DIMENSIONS W/O TILT					
height	in	86 5/8	92 5/16	92 1/8	
width	in	66 1/2	73 7/16	78 3/4	
depth	in	76 3/4	83 11/16	85 7/16	
shipping weight	lbs	6239	7518	8179	
SHIPPING DIMENSIONS W/ TILT					
height	in	96 1/16	98	98	
width	in	66 1/2	80 5/16	80 5/16	
depth	in	81 11/16	93 1/2	93 1/2	
shipping weight	lbs	7077	8289	8951	
AGENCY APPROVALS					
		CSA	CSA	CSA	

AY16-0030

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

© 2016 Alliance Laundry Systems LLC

Alliance Laundry Systems LLC
 Shepard Street
 Ripon, WI 54971
 1-877-724-0187

