Huebsch is the answer.

Coin Operated & Card Ready Front Load Washers and Stack Washer/Dryer







Huebsch is the answer.

Anybody can sell you laundry equipment and discuss the merits of each nut and bolt. However, at Huebsch, our priority is answering your questions about how working with us will make your business easier to run and more profitable.

Customers have selected Huebsch products for their ease of use, supreme durability and because owning a Huebsch product brings a service and support network that's unmatched within the industry. For profitability, reliability and ease of use, Huebsch is the answer.

Quality You Can Touch

I want equipment that sets my store apart and portrays a quality operation. What do Huebsch washers and dryers bring to the table to convey my message?

(H) Stainless steel inside and out.

Huebsch front load washers feature stainless steel inner and outer tubs that are durable and will stay looking good for years.



(H) Large, rugged doors.

Our washer's large 188.6 sq. in. door opening is a hit with customers, as it speeds the often awkward and time-consuming tasks of loading and unloading. In addition, the solid door features a durable piano style, steel hinge. Likewise, the dryer also has a rugged door and hinge with the industry's largest door opening, 2.06 sq. ft.

Convenience.

A frontmount supply dispenser automatically adds detergent, bleach and softener for customer convenience.



- Keeping control of quality.

Huebsch front load washers and dryers with a Micro-Display Control offer a time-remaining countdown, coin countdown and cycle status lights. Electro-mechanical control models offer basic wash and dry options and are simple to operate.



Keeping It Green

What makes these Huebsch machines green to save my operation some green?

(H) Low water use.

Huebsch front load washers offer owners a Water Saver Cycle that averages just 10.4 gallons of water per cycle. Low water use makes this



Huebsch machine the perfect replacement for water guzzling top load washers. Best of all, the washer is so efficient it's earned an ENERGY STAR® rating.

(H) High spin speed.

With a final spin of 1,000 RPM, Huebsch front load washers exert 300 G-Force on loads to remove more water. This is the same G-Force many top-ofthe-line large capacity washer-extractors exert in commercial laundry applications. The end results are greatly reduced drying times for customers and lower utility consumption for store owners.

(H) Fast drying times.

Huebsch's matching dryer delivers fast drying results that complement the front load washer's performance. A 7.0 cu. ft. cylinder with an 18 lb capacity offers ample space for large loads to tumble and produce fast drying times.



Space Savings

My laundry is short on space, how can I add washing and drying capacity?



(H) Huebsch space savers.

A stack washer/dryer gives your vended laundry all the benefits of a stand-alone washer and dryer pair in the space of one machine. The stack utilizes all the same connections as standard washer and dryers, so there's no special hookups required.

Unmatched Durability

I'm investing a large sum in my coin laundry, and want peace of mind my equipment will last well into the future. What sets Huebsch apart in terms of reliability?

(H) Rugged inside and out.

Huebsch's front load washer boasts a rugged design, including a cast aluminum trunnion and bearing housing as well as four heavy-duty shock absorbers.



(A) Heavy duty power.

Our front load washer is powered by a heavy-duty 1 horsepower motor, while Huebsch dryers feature a 1/3 horsepower commercial quality motor.

(H) Versatility.

For customers not replacing conventional top load washers, gravity drain (drain valve) models are available.

(H) Not just standing behind our equipment, but standing beside you and your business.



Our made-in-America product comes with an industry-leading

bond. The entire machine receives Huebsch's standard three-year warranty. In addition, Huebsch has more service representatives in the field than most brands have in their whole organization.



HFNBYRSP112TW01 HFNBCRSP112TW01 HFNBYFSP112CW01 HFNBCFSP112TW01

Washers	HFNBCFSG112TW01	HFNS
Cycles E-Mech	N/A	Normal Permanent Press Delicate
MDC	Normal/Hot Normal/Warm Permanent Press/Warm Delicate/Cold	N/A
Water Temperatures	Hot Warm Cold	Hot Warm Cold
Stainless Steel Washtub	2.84 cu. ft.	2.84 cu. ft.
Water Pressure - psi (bar)	Fill 20-120 (1.4/8.3)	Fill 20-120 (1.4/8.3)
Wash/Tumble - RPM	41, 50	41, 50
Distribution/Pump - RPM	90	90
Spin Speeds - RPM	1000, 650, 500	1000, 650, 500
Activation	Coin/Card Operated	Coin Operated
Dispenser	Detergent, Liquid Bleach, Liquid Softener	Detergent, Liquid Bleach, Liquid Softener
Motor* - HP	Variable Speed Induction, 1	Variable Speed Induction, 1
Color	White	White
Electrical Specs. [†]	120/60/1 • 15 amp	120/60/1 • 15 amp
Width - in (mm)	26 7/8" (683)	26 7/8" (683)
Depth - in (mm)	28" (711)	28" (711)
Height** - in (mm)	43" (1092)	43" (1092)
Net Weight - Ib (kg)	240 (109) Rear Control 250 (113) Front Control	240 (109)
Shipping Weight - Ib (kg)	260 (118) Rear Control 270 (123) Front Control	260 (118)
Agency Approvals	cULus	cULus

* Motor: 1 HP reversing, permanently lubricated with a built-in electronic protector.

** Heights may vary slightly depending on leveling adjustments.

[†] Electrical requirements: Grounded 3-wire, 120V, 60 Hz AC, 15 amp circuit separately fused.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

Printed in the U.S.A.

©Copyright 2013 Alliance Laundry Systems LLC

Elec: HTEBCFSP172TW01

Stack Washer/Dryers

Gas: HTGBYFSP112TW01 HTGBCFSP112TW01

Width - in (mm)	26 7/8" (683)
Depth - in (mm)	28" (711)
Height* - in (mm)	76 5/8" (1946)
Color	White
Net Weight - Ib (kg)	Elec: 360 (163) Gas: 365 (166)
Shipping Weight - Ib (kg)	Elec: 390 (177) Gas: 395 (179)
Agency Approvals	Elec: cULus Gas: cCSAus

Dryer (Specifications for Stack Model)

Cycles	High
	Medium
	Low
	Delicate
Cylinder volume - cu.ft. (liters)	7.0 (201)
Motor - HP	1/3, 5.5 amp
Heating Element***	US: 5350W, 240V
	4750W, 208V
	Canada: 5000W 240V
	4250W 208V
Btu Per Hour	25,000 (6,300 kcal)
Type of Gas (Gas models only)	Factory-equipped natural/
	mixed gas. Convertible to LP.
Utility Connections	3/8" NPT
Air Outlet Diameter - in (mm)	4" (102)
Exhaust Airflow - cfm (m ³ hr) ^{††}	220 (374)
Max Static Back Pressure	0.6" WC
Elec. Specifications and	Elec: 120/240/60/1 • 30 amp
Circuit Requirements	Gas: 120/60/1 • 15 amp
Agency Approvals	Elec: cULus
	Gas: CSA Flame, CSA Star

*** 208V operation requires field conversion.

^{††} Measured at point of exit from dryer.

See washer and dryer charts for detailed specifications.

ADA Compliant



Alliance Laundry Systems, Shepard Street, Ripon, WI 54971 Telephone: 1-800-553-5120