Speed Queen

COMMERCIAL/HOMESTYLE

Topload Washers & Dryers

LWS01 LES17/LGS17



Speed Queen®

OUR STRENGTH COMES FROM WITHIN

Commercial/Homestyle Washer & Dryer Specifications





LWS01

Single Speed • 7 cycles • 3 Wash/Rinse Temperatures Large Blue Porcelain Tub • Bleach Dispenser Variable Rotary Water Level Control • Curved Vane Agitator LES17/LGS17
6 Cycles • Polyester Lint Filter
3 Position Fabric Selector • Optional Drying Rack
Reversible Door

Model	LWS01
Speeds	1
Cycles	3
Regular	•
Permanent Press	•
Delicate	•
Water Temp.	3
Hot/Cold	•
Warm/Cold	•
Cold/Cold	•
Features	
Water Levels	Variable Rotary
Curved Vane Agitator	•
Basket Volume (DOE Cu. Ft.)	2.94 (Large)
Top & Lid Finish	Tuff Guard
Blue Porcelain Tub	•
Bleach Dispenser	•
Colors	White
Self-Adjusting Rear Leveling Legs	•
Dimensions	
Width (in/mm)	25 5/8" (651 mm)
Depth (in/mm)	28" (711 mm)
Machine Height (in/mm)	43" (1092 mm)
Cabinet Height (in/mm)	36" (910 mm)
Approx. Weight	177 lb (80 kg)
Agency Approval	UL
Motor: 1/2 HP reversing, permanently lubricated with a built-in automatic thermal overload protector. Electrical Requirements: Grounded 3-wire, 120V, 60 Hz AC, 15 amp circuit separately fused. Heights may vary slightly depending on leveling adjustments. Speed Queen's continuing commitment to quality products may mean a change in specifications without notice.	

Commercial Quality

Built tough to stay that
way. For over 30 years,
Speed Queen has served
the coin-operated laundry
industry and continues to
lead in customer satisfaction. Speed Queen homestyle washers and dryers
feature many of the same
rugged, reliable parts
found in the coin-operated
machines, so they're
built to last.



Model	LES17/LGS17
Cylinder Volume	7.0 cu. ft.
Cycles	6 6
Auto	
Regular/Delicate	
More Dry	• •
Less Dry	• •
Permanent Press/Kr	nits
More Dry	• •
Less Dry	• •
Time	
More Dry	• •
Less Dry	• •
Features	
Cylinder Interior	Galvanized Steel
180° Side Swing	• •
Reversible Door	
Secured	• •
Lint Filter	NAU 1
Colors	White
Energy Input Elec:	5350W
Energy Input Gas:	22,500Btu
Temperature	3 3
Delicate	•
No Heat	•
Regular/Perm Press	• •
Dimensions	00.7/01/(000
Width (in/mm)	26 7/8" (683 mm)
Depth (in/mm)	28" (711 mm)
Machine Height (in/mm)	43" (1092 mm)
Cabinet Height (in/mm)	36" (910 mm)
Approx. Weight	Gas: 135 lb (61 kg) Elec: 130 lb (56 kg)
Agency Approval	UL, AGA
Motor: 1/3 HP, permanent in automatic thermal overla	ly lubricated with a built- oad protector.
Electrical Requirements: ((neutral conductor grounda amp circuit separately fuse grounded (earth) wire syste amp circuit separately fuse	ed), 120/240V, 60 Hz AC, 30 d. (Gas) 2 wire plus

amp circuit separately fused. Heights may vary slightly

Speed Queen's continuing commitment to quality

products may mean a change in specifications

depending on leveling adjustments.



Commercial Built Better To Last Longer!