

Speed Queen

COMMERCIAL/HOMESTYLE
Topload WASHERS & DRYERS

LWS01
LES17/LCS17



Speed Queen®

OUR STRENGTH COMES FROM WITHIN

COMMERCIAL/HOMESTYLE WASHER & DRYER SPECIFICATIONS



LWS01
Single Speed • 7 cycles • 3 Wash/Rinse Temperatures
Large Blue Porcelain Tub • Bleach Dispenser
Variable Rotary Water Level Control • Curved Vane Agitator

LES17/LGS17
6 Cycles • Polyester Lint Filter
3 Position Fabric Selector • Optional Drying Rack
• Reversible Door

Model	LWS01
Speeds	1
Cycles	7
	<ul style="list-style-type: none"> • Reg.-Extra Clean • Reg.-Normal • Reg.-Light • Perm Press-Normal • Perm Press-Light • Delicate-Normal • Delicate-Light
Water Temp.	3
	<ul style="list-style-type: none"> • Hot/Cold • Warm/Cold • Cold/Cold
Features	
Water Levels	Variable Rotary
Agitator	Curved Vane
Basket Volume (DOE Cu. Ft.)	2.94 (Large)
Top & Lid Finish	Tuff Guard
Tub	Blue Porcelain
Dispenser	Bleach
Color	White
Rear Leveling Legs	Self-Adjusting
Dimensions	
Width - in (mm)	25 5/8" (651)
Depth - in (mm)	28" (711)
Height - in (mm)	43" (1092)
Cabinet Height - in (mm)	36" (910)
Approx. Weight - lb (kg)	177 (80)
Agency Approvals	UL
<p>Motor: 1/2 HP reversing, permanently lubricated with a built-in automatic thermal overload protector.</p> <p>Electrical Requirements: Grounded 3-wire, 120V, 60 Hz AC, 15 amp circuit separately fused. Heights may vary slightly depending on leveling adjustments.</p>	

Speed Queen's continuing commitment to quality products may mean a change in specifications without notice.

COMMERCIAL QUALITY

Built tough to stay that way. The No. 1 supplier of commercial coin-operated laundry equipment, Speed Queen continues to lead in customer satisfaction. Speed Queen homestyle washers and dryers feature many of the same rugged, reliable parts found in the coin-operated machines, so they're built to last.



Model	LES17/LGS17
Cylinder Volume	7.0 cu. ft.
Cycles	6
Auto	
Regular/Delicate	<ul style="list-style-type: none"> • More Dry • Less Dry
Permanent Press/Knits	<ul style="list-style-type: none"> • More Dry • Less Dry
Time	<ul style="list-style-type: none"> • More Dry • Less Dry
Temperature	3
	<ul style="list-style-type: none"> • Delicate • No Heat • Reg./Perm Press
Features	
Cylinder Interior	Galvanized Steel
Door	180° Side Swing Reversible
Lint Filter	Secured
Color	White
Energy Input Elec:	5350W
Gas:	22,500Btu
Dimensions	
Width - in (mm)	26 7/8" (683)
Depth - in (mm)	28" (711)
Height - in (mm)	43" (1092)
Cabinet Height - in (mm)	36" (910)
Approx. Weight - lb (kg)	Gas: 135 (61) Elec: 130 (59)
Agency Approvals	UL, CSA Star
<p>Motor: 1/3 HP, permanently lubricated with a built-in automatic thermal overload protector.</p> <p>Electrical Requirements: (Elec.) 3 wire system (neutral conductor grounded), 120/240V, 60 Hz AC, 30 amp circuit separately fused. (Gas) 2 wire plus grounded (earth) wire system, 120V, 60 Hz AC, 15 amp circuit separately fused. Heights may vary slightly depending on leveling adjustments.</p>	

The quality management systems at all Alliance Laundry Systems manufacturing facilities are registered as ISO 9001:2000 compliant.

© Copyright 2004 Alliance Laundry Systems LL C

Commercial Built Better To Last Longer!