FRONT LOAD WASHERS

Speed Queen®

RENOWNED FOR COMMERCIAL-GRADE CONSTRUCTION.



EXTRA-LARGE 2.84 CU. FT. STAINLESS STEEL INNER AND OUTER TUB

- Constructed for increased washing performance and higher water extraction
- Saves energy, time and money

EXTRA-LARGE 15.5" DOOR OPENING

Allows easy loading and unloading

COMMERCIAL, HEAVY-DUTY SUSPENSION SYSTEM

- Constructed with four commercial, heavy-duty shock absorbers
- Adds strength and durability
- Limits out-of-balance issues

DOOR OPENING HIGHER THAN NON-PEDESTAL COMPETITIVE MODELS

• Easier to load and unload clothes

VARIABLE-SPEED INDUCTION MOTOR WITH INVERTER DRIVE

• Offers a 300 G-Force and 1000 RPM spin speed for optimum water extraction and outstanding performance

THREE-COAT, COMMERCIAL-GRADE STEEL CABINET

• Constructed with a galvanized metal cabinet and an extra E coat dip before the final paint for a long-lasting finish

INDUSTRY-LEADING, TRANSFERRABLE WARRANTY

- Three years parts & labor
- 5 years on motor & cabinet bearing and assembly*

* Limited. See Speed Queen warranty bond for details.



FRONT LOAD WASHER SPECIFICATIONS

Color: While··3 Stainless Steel Baffles··Stainless Steel Baffles··Stainless Steel Impe··15 1/2' Door Opening··10' Stainless Steel Hinge··Galvanized Steel Cabinet··Front Controls··Rear Controls··Stainless Steel1.3/8' x 26 7/8'2.84Overall Dimensions - M x W x D1.3/8' x 26 7/8'36'Overall Dimensions - M x W x D260250Work Surface Height - in41 3/8'36'Approximate Shipping Weight - in260200/60 HZAC 15 AmpNotor HP11Spin Speeds - RPM500, 650, 1000500, 650, 1000Fill Hoses Included··ADA Compliant··Jourd State Option··Stainless Deed Motor HP··Fill Hoses Included··Jourd Diagness··Jourd Diagness··State Speed··State Speed··State Option··State Option··State Option··State Option··State Option··State Speed··State Speed··State Option··State Option··State Option··	Model	AFN50F 📑	AFN50R 📑
Stoinless Steel Outer Drainhub··15 1/2' Door Opening··10' Stoinless Steel Hinge··Galvanized Steel Cabinet··Front Controls··Rear Controls2.842.84Voralt Dimensions -41.3/8" x 26.7/8" x 28"Vork Surface Height - in41.3/8" x 26.7/8" x 28"Vork Surface Height - in41.3/8" x 26.7/8" x 28"Vork Surface Height - in41.3/8"Stoinless Steel Weight - ib260Electrical Requirements Breaker Size120V/60 HzAC 15 AmpStoinless Included·ADA Compliant·ADA Compliant·Stainless Speed Motor HP·Stainless Steel Speeds - RPM·Stoinless Support Tiff Guard Coated Top·Yarable Speed Induction Motor·Stainless Steel Speed Steel·Yarable Speed Induction Motor·Stoinless Steel Speed Steel·Yarable Speed Induction Motor·Stoinless Steel Speed Stution Dispenser·Yarable Speed Induction Dispenser·Stainless Option·Yarable Speed Induction Dispenser·Stainless Steel Soution Dispenser·Yarable Speed Induction Dispenser·Yarable Speed Induction Dispenser·Yarable Speed Induction Dispenser·Yarable Speed Soution Dispenser·Yarable Speed Soution Dispenser	Color: White	V	v
Outer DraintubImage: ControlsImage: Controls10' Stainless Steel HingeImage: ControlsImage: ControlsFront ControlsImage: ControlsImage: ControlsRear ControlsImage: ControlsImage: ControlsStainless Steel Washinub Volume - cu. ft.2.842.84Overall Dimensions - think with D41.3/8" x 26.7/8" x 28"Work Surface Height - in41.3/8"36"Approximate Shipping260250Berder Requirements1.20V/60 HZAC1.20V/60 HZACElectrical Requirements5.00, 650, 1000500, 650, 1000Fill Hoses IncludedImage: ControlsImage: ControlsADA CompliantImage: ControlsImage: ControlsSolo G-Force High SpeedImage: ControlsImage: ControlsSuffice SpeedImage: ControlsImage: ControlsSuffice SpeedImage: ControlsImage: ControlsSolo G-Force High SpeedImage: ControlsImage: ControlsSuffice SpeedImage: Control SpeedImage: Control SpeedSuffice Sp	3 Stainless Steel Baffles	V	v
10' Stainless Steel Hinge··Galvanized Steel Cabinet··Front Controls··Rear Controls··Stainless Steel Washtub Volume - cu. ft.2.842.84Overall Dimensions - H x W x D2.8436"Overall Dimensions - H x W x D41 3/8" x 26 7/8" x 28"43" x 26 7/8" x 28"Work Surface Height - in41 3/8"36"Approximate Shipping Weight - ib260250Electrical Requirements Breaker Size120V/60 HzAC 15 Amp120V/60 HzAC 15 AmpMotor HP11Spin Speeds - RPM500, 650, 1000500, 650, 1000Fill Hoses Included··ADA Compliant··Staine Speed Induction Motor··Star Rinse Option··Cycles88Average Water Coyles88Average Water Cycles10.310.3		V	V
Galvanized Steel Cabinet··Galvanized Steel Cabinet··Front Controls··Rear Controls··Stainless Steel Washtub Volume - cu. ft.2.842.84Overall Dimensions - H x W x D2.8436"Overall Dimensions - H x W x D41 3/8" x 26 7/8" x 28"43" x 26 7/8" x 28"Vork Surface Height - in41 3/8"36"Approximate Shipping Weight - ib260250Electrical Requirements Breaker Size120V/60 HzAC 15 Amp120V/60 HzAC 16 AmpMotor HP11Spin Speeds - RPM500, 650, 1000500, 650, 1000Fill Hoses Included··ADA Compliant··S00 G-Force High Speed Varier Extraction··Variable Speed Tuff Guard Coated Top··Kird Rinse Option···Sylup Cylinder Holes··Furg Rinse Option··Solution Dispenser88Average Water Coyles88Average Water Coyles10.310.3	15 1/2" Door Opening	V	v
Front Controls··Rear Controls··Stainless Steel Washtub Volume - cu. ft.2.842.84Overall Dimensions - H x W x D41 3/8" x 26 7/8" x 28"43" x 26 7/8" x 28"Work Surface Height - in41 3/8"36"Approximate Shipping Weight - ib260250Electrical Requirements Breaker Size120V/60 HzAC 15 Amp120V/60 HzAC 15 AmpMotor HP11Spin Speeds - RPM500, 650, 1000500, 650, 1000Fill Hoses Included··ADA Compliant··Sol G-Force High Speed Water Extraction··Sylap Cylinder Holes··Luft Guard Coated Top··Extra Rinse Option··Cycle Indicator Light··Fore Compartment Solution Dispenser88Average Water Cycles88Average Water Cycles10.310.3	10" Stainless Steel Hinge	V	v
Rear ControlsImage: ControlsStoinless Steel Washtub Volume - cu. ft.2.842.84Overall Dimensions - H x W x D41 3/8' x 26 7/8' x 28'43'' x 26 7/8'' x 28''Work Surface Height - in41 3/8''36''Approximate Shipping Weight - ib260250Electrical Requirements Breaker Size120V/60 HzAC 15 Amp120V/60 HzAC 15 AmpMotor HP11Spin Speeds - RPM500, 650, 1000500, 650, 1000Fill Hoses IncludedImage: Colored High Speed Water ExtractionImage: Colored High Speed Image: Colored High SpeedVariable Speed Induction MotorImage: Colored High Speed Image: Colored High SpeedImage: Colored High Speed Image: Colored High SpeedVariable Speed Induction MotorImage: Colored High Speed Image: Colored High SpeedImage: Colored High Speed Image: Colored High SpeedVariable Speed Induction MotorImage: Colored High Speed Image: Colored High SpeedImage: Colored High Speed Image: Colored High SpeedVariable Speed Induction MotorImage: Colored High Speed Image: Colored High SpeedImage: Colored High Speed Image: Colored High SpeedImage: Colored High SpeedVariable Speed Induction MotorImage: Colored High Speed Image: Colored High SpeedImage: Colored High Speed Image: Colored High SpeedImage: Colored High SpeedVariable Speed Induction MotorImage: Colored High Speed Image: Colored High SpeedImage: Colored High SpeedImage: Colored High SpeedCycle Indicator Light Solution DispenserImage: Color	Galvanized Steel Cabinet	V	v
Stainless Steel Washtub Volume - cu. ft.2.842.84Overall Dimensions - H x W x D41 3/8" x 26 7/8" x 28"43" x 26 7/8" x 28"Work Surface Height - in41 3/8"36"Approximate Shipping Weight - Ib260250Electrical Requirements Breaker Size120V/60 HzAC 15 Amp120V/60 HzAC 15 AmpMotor HP11Spin Speeds - RPM500, 650, 1000500, 650, 1000Fill Hoses IncludedADA Compliant300 G-Force High Speed Water ExtractionYariable Speed Induction MotorTuff Guard Coated Top Solution DispenserCycle Indicator Light Solution DispenserAverage Water Cycles88Average Water Culs10.310.3	Front Controls	V	
Washtub Volume - cu. ft.International and the second s	Rear Controls		v
H x W x Dx 28°x 28°Work Surface Height - in41 3/8"36"Approximate Shipping260250Electrical Requirements120V/60 HzAC 15 Amp120V/60 HzAC 15 AmpBreaker Size120V/60 HzAC 15 Amp120V/60 HzAC 15 AmpMotor HP11Spin Speeds - RPM500, 650, 1000500, 650, 1000Fill Hoses IncludedADA Compliant300 G-Force High Speed Water ExtractionVariable Speed Induction Motor5,499 Cylinder HolesTuff Guard Coated TopExtra Rinse OptionCycle Indicator Light Solution Dispenser88Average Water Cycles88Average Water Cuse10.310.3		2.84	2.84
Approximate Shipping Weight - Ib260250Electrical Requirements Breaker Size120V/60 HzAC 15 Amp120V/60 HzAC 15 AmpMotor HP11Spin Speeds - RPM500, 650, 1000500, 650, 1000Fill Hoses IncludedADA Compliant300 G-Force High Speed Water ExtractionYariable Speed Induction Motor5,499 Cylinder HolesTuff Guard Coated TopExtra Rinse OptionCycle Indicator Light Solution DispenserCycles88Average Water Consumption - Gallons10.3I0.3			43″ x 26 7/8″ x 28″
Weight - IbHandbackBase ReservesElectrical Requirements Breaker Size120V/60 HzAC 15 Amp120V/60 HzAC 15 AmpMotor HP11Spin Speeds - RPM500, 650, 1000500, 650, 1000Fill Hoses IncludedIIADA CompliantII300 G-Force High Speed Water ExtractionIIYariable Speed Induction MotorII5,499 Cylinder HolesIIExtra Rinse OptionIICycle Indicator Light Solution DispenserIICycles88Average Water Cosmuption - GallonsI0.3I0.3	Work Surface Height - in	41 3/8″	36″
Breaker Size15 Amp15 AmpMotor HP11Spin Speeds - RPM500, 650, 1000500, 650, 1000Fill Hoses Included✓✓ADA Compliant✓✓300 G-Force High Speed Water Extraction✓✓Yariable Speed Induction Motor✓✓5,499 Cylinder Holes✓✓Extra Rinse Option✓✓Cycle Indicator Light Solution Dispenser✓✓Free Compartment Solution Dispenser10.310.3		260	250
Spin Speeds - RPM500, 650, 1000500, 650, 1000Fill Hoses IncludedADA Compliant300 G-Force High Speed Water ExtractionYariable Speed Induction Motor5,499 Cylinder HolesTuff Guard Coated TopExtra Rinse OptionCycle Indicator LightSolution Dispenser88Average Water Cycles10.310.3	Electrical Requirements Breaker Size		
Fill Hoses IncludedImage: Constraint of the section of t	Motor HP	1	1
ADA CompliantImage: CompliantADA CompliantImage: Compliant300 G-Force High Speed Water ExtractionImage: CompliantVariable Speed Induction MotorImage: Compliant5,499 Cylinder HolesImage: Compliant5,499 Cylinder HolesImage: CompliantImage: Compliant Coated TopImage: CompliantExtra Rinse OptionImage: CompliantCycle Indicator LightImage: CompliantThree Compartment Solution DispenserImage: CompliantCycles8Average Water 	Spin Speeds - RPM	500, 650, 1000	500, 650, 1000
300 G-Force High Speed Water Extraction·300 G-Force High Speed Water Extraction·Variable Speed Induction Motor·5,499 Cylinder Holes·5,499 Cylinder Holes·Tuff Guard Coated Top·Extra Rinse Option·Cycle Indicator Light·Three Compartment Solution Dispenser·Cycles8Average Water Consumption - GallonsI0.3Interest Compartment Solution CompartmentInterest Compartment Solution CompartmentCycles·Solution Compartment Solution CompartmentInterest Compartment Solution CompartmentCycles·Solution Compartment Solution Compartment·Solution Compartment Solution Compartment Solution Compartment·	Fill Hoses Included	V	v
Water ExtractionProvide the second secon	ADA Compliant	V	v
Induction MotorImage: Constraint of the second		~	V
Tuff Guard Coated Top✓✓Extra Rinse Option✓✓Cycle Indicator Light✓✓Three Compartment Solution Dispenser✓✓Cycles88Average Water Consumption - GallonsI0.3I0.3		~	~
Extra Rinse Option··Cycle Indicator Light··Three Compartment Solution Dispenser··Cycles88Average Water Consumption - Gallons10.310.3	5,499 Cylinder Holes	V	v
Cycle Indicator Light✓Three Compartment Solution Dispenser✓Cycles8Average Water Consumption - Gallons10.3	Tuff Guard Coated Top	V	V
Three Compartment Solution DispenserCycles88Average Water Consumption - Gallons10.310.3	Extra Rinse Option	V	v
Solution Dispenser Image: Construction of the second sec	Cycle Indicator Light	V	v
Average Water 10.3 10.3 Consumption - Gallons 10.3		V	V
Consumption - Gallons	Cycles	8	8
Agency Approvals CULus CULus		10.3	10.3
	Agency Approvals	cULus	cULus


Made in America since 1908, Speed Queen machines are renowned for their consistently powerful performance. Whether designed for homeowners or for commercial laundries, our washers and dryers are built to the highest standards of durability and dependability – and backed by superior customer service.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000. Printed in the USA.

speedqueen.com





AFN50F (Shown on front) – 8 Cycles, ADA Compliant, ENERGY STAR $^{\otimes}$ Qualified, Front Control





 $\mathsf{AFN5OR}-\mathsf{8}$ Cycles, ADA Compliant, ENERGY STAR® Qualified, Rear Control











AFN50R - Rear Control Model



© 2014 Alliance Laundry Systems LLC AR14-0016