

## ON-PREMISES SINGLE TUMBLE DRYER

50-75lb



### FEATURES

- Easy-to-use digital control
- Electric, gas, and steam heating
- Large door opening for easy loading and unloading
- Galvanized cylinder
- Radial airflow
- Large self-cleaning lint screen

### OPTIONS

- Full OPL microprocessor control
- Reversing cylinder to avoid tangling of large items
- Stainless steel cylinder
- Stainless steel front panel
- Sensodry+® over-dry prevention technology lowers energy, utility, and linen replacement costs
- SafeTech™ Fire Suppression System, a multi-port water manifold system, will saturate linens in an unlikely event of fire within the cylinder



FAST DRYING  
CYCLES



EASY OPERATION



LARGE DOOR  
OPENING

TYPE		PT50	PT75
<b>CAPACITY</b>			
capacity	lbs	50	75
cylinder volume	cu ft	18.6	22.4
cylinder diameter	in	37	37
<b>AIRFLOW</b>			
60 Hz	cfm	750	750
<b>DRYING AVERAGE</b>			
gas heating	lbs/min	1	1.36
electric heating	lbs/min	0.88	0.84
<b>MOTOR</b>			
fan	hp	0.5	0.75
drive	hp	0.5	0.75
<b>ELECTRICAL CONNECTION</b>			
<b>gas and steam models</b>		Non Rev Amps, (Rev Amps)	Non Rev Amps, (Rev Amps)
120/208-240/60/1 2W/3W+G		(12/6.5)	(13/7)
120/60/1 2W+G		9.3	13.8
200-208/240/60/1 2W+G		5.1/5.1	7.6/7.6
200-208/240/60/3 3W+G		2.8/2.8, (4.0/4.0)	3.8/3.8, (4.3/4.3)
380/60/3 3W+G		1.6, (2.0)	1.8, (2.1)
*STEAM ONLY* 440/60/3 3W+G		1.4, (1.9)	1.9, (2.1)
460-480/60/3 3W+G		1.4, (1.9)	1.9, (2.1)
<b>electric models</b>			
200-208/60/3 3W+G		89, (88)	89, (88)
240/60/3 3W+G		79, (78)	79, (78)
380/60/3 3W+G		47, (48)	47, (48)
440/60/3 3W+G		41, (41)	41, (41)
480/60/3 3W+G		38, (38)	38, (38)
<b>GAS HEATING</b>			
energy	kBTU/h	178	210.3
gas connection	NPT	.75"	.75"
<b>STEAM HEATING</b>			
high pressure 100psi	kBTU/h	178	210.3
steam connection	NPT	.75"	.75"
<b>ELECTRIC HEATING</b>			
energy	kW	30	30
<b>EXHAUST</b>			
	in	8	8
<b>DIMENSIONS</b>			
height	in	76.62	76.62
width	in	38.62	38.62
depth	in	48.25	54.25
net weight	lbs	545	615
<b>SHIPPING DIMENSIONS</b>			
height	in	81	81
width	in	41.5	41.5
depth	in	52.1	56.4
shipping weight	lbs	602	677
<b>AGENCY APPROVALS</b>		cCSAUs	cCSAUs

AY15-0006

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

© 2015 Alliance Laundry Systems LLC

Alliance Laundry Systems LLC  
Shepard Street  
Ripon, WI 54971  
1-877-724-0187

**primus**

laundry equipment