



ON-PREMISES RIGID MOUNT WASHER-EXTRACTOR

20, 25, and 30lb





FEATURES

- Rigid mounted, 100 or 200 G-Force options
- Stainless steel top, front, and side panels
- Stainless steel cylinder and tub
- Patented Cascade[™] cylinder for better washability
- XControl+ fully programmable control
- Patented Soap Hopper
- Large drain valve
- Front access to vital parts for easy maintenance
- Large door opening for easy loading and unloading
- USB plug on the back panel and control board
- 10 Year Warranty: frame, outer tub, cylinder shaft assembly, bearing housing, cylinder bearings and bearing seals



OPTIONS

- Third water inlet
- Steam heating

3 YEAR PARTS WARRANTY







ТҮРЕ		PA20	PA25	PA30
INNER CYLINDER				
maximum capacity	lbs	20	25	30
volume	cu ft	2.6	3.7	4.8
diameter	in	20.9	24.4	24.4
CYLINDER SPEED				
wash	rpm	50	46	46
extraction	rpm	820	760	760
G-FORCE		200	200	200
HEATING				
steam	psi	15-116	15-116	15-116
Sound pressure level	dB (A)	< 65	< 65	< 65
Water valves connection	NPT*	3/4"	3/4"	3/4"
Water pressure	psi	15-116	15-116	15-116
Recommended water pressure	psi	45-75	45-75	45-75
Water inlet (each)	g/min	5.28	5.28	5.28
Drain valve	in	3	3	3
Flow amount w/drain valve	g/min	55.5	55.5	55.5
floor to drain outlet center	in	3.46	3.85	3.85
side to drain outlet center	in	6.53	8.85	8.85
Steam valve connection	BSP	1/2"	1/2"	1/2"
Steam pressure	psi	15-75	15-75	15-75
VOLTAGE				
120/60/1	circuit breaker – FLA	15-8.0	15-11. <i>7</i>	15-13.3
208-240/60/1	circuit breaker – FLA	10-4.4	10-6.3	10-7.2
DIMENSIONS				
height	in	43.9	48.2	48.2
width	in	26	29.5	29.5
depth	in	30.9	30.9	35.4
net weight	lbs	298	375	419
SHIPPING DIMENSIONS				
height	in	49	53.3	53.3
width	in	28	31.5	31.5
depth	in	32.9	32.9	37.4
shipping weight	lbs	320	408	441
AGENCY APPROVALS		_C CSA _{US}	_C CSA _{US}	_C CSA _{US}
*Fill Hoses provided to convert BSP at machine to NPT supply connection.				

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.





