



VENDED DRYER

Huebsch® vended dryers are durably constructed and extensively tested to ensure optimal performance even when faced with your customers toughest loads. All Huebsch vended dryers feature a durable porcelain enamel top to maintain a lustrous appearance in even the toughest environments.

FAST DRYING TIMES

Huebsch dryers offer a 7.0 cu. ft. cylinder with an 18 lb capacity offers ample space for large loads to tumble and produce fast drying times, while lowering utility consumption.

LARGE, REVERSIBLE DOORS

Our dryers boast the industry's largest door opening at 2.06 sq. ft. Dryer doors also are reversible, making it easy to customize your laundry for your customers' convenience.

SOLID BASE

Huebsch dryers are built on sturdy steel bases to ensure years of worry-free performance.

UNMATCHED DURABILITY

Our vended dryer is manufactured at our Ripon, WI headquarters. The entire machine receives Huebsch's standard three-year warranty. In addition, Huebsch has more service representatives in the field than most brands have in their whole organization.

*Parts only, labor not included. See Huebsch Warranty Bond for specifics.



MICRO-DISPLAY CONTROL



The Micro-Display Control features a time-remaining countdown, coin countdown and cycle status lights.

VENDED DRYER

Specifications	Front Control	Rear Control		
Available Controls	MDC	MDC	Coin Slide	
Models	Electric	HDEBXAGS171CW01 HDEBCAGS171TW01 HDEBYAGS171CW01	HDET07WF HDEY07WF	HDE907WF HDE907WF1502 HDE907WF1702
	Gas	HDGBXAGS111CW01 HDGBCAGS111TW01 HDGBYAGS111CW01	HDGT09WF HDGY09WF	HDG909WF HDG909WF1102
Capacity - lb (kg)	18 (8.2)	18 (8.2)		
Cylinder Volume - cu. Ft. (liters)	7.0 (198)	7.0 (198)		
Width - in (mm)	26 7/8 (683)	26 7/8 (683)		
Depth - in (mm)	28 (711)	28 (711)		
Height - in (mm)	44 3/8 (1126)	43 (1092)		
Motor Size - HP (kw)	1/3 (0.25)	1/3 (0.25)		
Available Heat Sources	Electric or Gas	Electric or Gas		
Available Heating Element (Electric W)	4750 @ 208V 5350 @ 240V	4750 @ 208V 5350 @ 240V		
Gas Inlet Connection - in (mm)	3/8 (9.5)	3/8 (9.5)		
Gas Consumption - BTU/Hr	25,000	25,000		
Exhaust Outlet Diameter - in (mm)	4 (102)	4 (102)		
Exhaust Airflow - cfm (liters/sec)	220 (105)	220 (105)		
Available Cycles*	High, Medium, Low, Delicates	High, Medium, Low, Delicates		
Cycle Indicator Lights	Yes	Yes		
Cylinder Finish	Galvanized	Galvanized		
Available Colors	White	White		
Door Type (Solid/Window)	Solid	Solid		
Available Electrical Requirements - (Voltage/Hz/Ph)	Electric: 120/240/60/1 - 30 Amp Electric: 120/208/60/1 - 30 Amp Gas: 120/60/1 - 15 Amp	Electric: 120/240/60/1 - 30 Amp Electric: 120/208/60/1 - 30 Amp Gas: 120/60/1 - 15 Amp		
Net Weight - lb (kg)	Elec/Gas 150/155 (68/70)	Elec/Gas 135/140 (61/64)		
Shipping Weight - lb (kg)	Elec/Gas 160/165 (73/75)	Elec/Gas 145/150 (66/68)		
Shipping Width - in (mm)	29 (737)	29 (737)		
Shipping Depth - in (mm)	32 3/4 (832)	32 3/4 (832)		
Shipping Height - in (mm)	45 1/2 (1156)	45 1/2 (1156)		
Available Agency Approvals	Elec: ^{UL} _{C US} , Gas: ^C _{CSA US}	Elec: ^{UL} _{C US} , Gas: ^C _{CSA US}		

* Information shown applies to highest end control available

Note: Not all options are available for all models. Twelfth digit in model number indicates US or Canadian unit. C=Canada & T=US. Refer to the price list for the available models and options.

Front control unit is ADA Compliant

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

©Copyright 2015 Alliance Laundry Systems LLC

Alliance Laundry Systems LLC
Shepard Street
Ripon, WI 54971
1-800-553-5120
huebsch.com

AH15-0025

