MS, IER EAR HARDMOUNT



SERIOUS ABOUT LAUNDRY.





# UC SERIES HARDMOUNT WASHER-EXTRACTORS 20-80 LB

As the leading manufacturer of on-premises laundry equipment, UniMac® offers more than 60 years of incomparable quality and long-lasting performance. Our UC series is built with unyielding construction to ensure industrial strength. Our cutting-edge innovations and technologies reduce costs and maximize throughput. And we're constantly improving. It's all part of our commitment to providing the lowest cost of ownership in the industry.

#### LOWER YOUR COSTS WITH UNIMAC

- Faster extraction technology spins up to 200 G-Force to remove more water during each load, resulting in shorter drying times and lower energy bills.
- Advanced Inverter Drive proven technology and our proprietary design provide smooth, reliable
  power for optimal wash and extract performance. Unparalleled water and energy—saving you 33% in
  electricity versus previous models.
- Minimized sump design uses 11% less water while maintaining optimal cleaning.
- Patented Water Guardian leak detection reduces water consumption by detecting leaking fill or drain valves, identifying leaks before they cost your operation hundreds of dollars in wasted resources.

#### **OUR COMMITTMENT TO OPL**

Our customers are the direct focus of every product we manufacture and every decision we make. We make sure every piece of UniMac equipment comes with peace of mind and the support you need to help your business succeed. We are with you every step of the way for:

- · Support from a worldwide network of distributors and a team of trained technicians.
- · Service Parts Availability.
- Service training certification for distributors through Alliance Laundry Systems University.

#### INDUSTRY-LEADING DURABILITY

The washer-extractor's heavy-duty computer-optimized frame is designed to stand up to the toughest laundry conditions. It's stronger than ever before, has a quieter operation and balances loads more efficiently.





Proudly based in Ripon, Wisconsin, USA, UniMac is dedicated to research, development and testing to provide equipment that delivers industrial strength and long-lasting quality. Our products undergo a 5-Stage Product Development Process and are pushed beyond their limits in our state-of-the-art test lab to ensure they exceed the toughest demands of the commercial environment and meet our customer's highest of standards.

#### BEST-IN-CLASS BEARING PROTECTION

UniMac® washer-extractors feature two close-tolerance ball bearings, permanently lubricated for trouble-free operation. Excluder seal and two triple-lip seals provide seven times the sealing power to isolate the bearings from water and chemicals.



#### THREE CONTROL OPTIONS

UniMac's flexibility is emphasized by the three levels of control available: M30, M9 and M4.

**M30 Control** – There are a total of 30 programs that you can modify to customize your laundry for specific needs.



Special features include cycle time remaining, temperature-controlled fill, cycle counter and test-cycle for diagnostics. Also features 30 programmable water levels to reduce water use. Easily programmed through control's infrared port.

**M9 Control** – Nine cycles that can be modified to meet your laundry's unique demands.

Three water levels and up to



five supply signals for automated dispensing of laundry chemicals. Cycle counter and test-cycle for self-diagnostics.

M4 Control – Four-cycle control for laundries with light soil and limited selection of linens. Limited diagnostic test.



### **WORRY-FREE PERFORMANCE**

For more than 60 years, UniMac laundry machines have set the industry standard for quality, durability and performance. A five-year warranty covers the frame, basket, shaft, bearings and seals from failure or breakage during normal operation due to defects in material or workmanship. A limited 3-year warranty is offered on all other parts.\*

\*Parts only, labor not included. See UniMac Warranty Bond for specifics.

#### UC SERIES — AT A GLANCE:

- Reduce dry-time and increase throughput with 200 G-Force extraction speed
- Computer-optimized frame design stronger than ever before with quieter operation
- Stainless steel top and front panel
- Three different control options (M30, M9 and M4) offer flexibility and enhanced laundry management
- Offered in five capacity options (20, 30, 40, 60 and 80 lb)
- . Heavy-duty bearings and seals
- Engineered for quick troubleshooting and ease of service
- Self-cleaning
   4-compartment dispenser
- Large heavy-duty loading door
- Steam and electric water heating options



## UC SERIES HARDMOUNT WASHER-EXTRACTORS 20-80 LB

SPECIFICATIONS				UC20	UC30	UC40	UC60	UC80
Control Option				M4, M9, M30	M4, M9, M30	M4, M9, M30	M4, M9, M30	M4, M9, M30
Capacity - Ib (kg)				20 (9)	30 (13.6)	40 (18)	60 (27)	80 (36)
Overall Width - in (mm)				26 (660)	29 (737)	30 5/8 (778)	34 3/16 (868)	41 1/2 (1054)
Overall Depth - in (mm)				30 1/4 (767)	34 9/16 (878)	39 3/4 (1009)	42 9/16 (1081)	48 5/8 (1234)
Overall Height - in (mm)				43 (1092)	45 (1143)	47 3/16 (1199)	49 7/8 (1267)	56 3/16 (1427)
Cylinder Diameter - in (mm)				21 (533)	24 (610)	26 1/4 (667)	30 (762)	36 (914)
Cylinder Depth - in (mm)				13 3/4 (349)	16 (406)	20 1/4 (514)	22 (559)	21 7/8 (555)
Cylinder Volume - cu. ft. (liters)				2.76 (78.1)	4.19 (118)	6.34 (180)	9.0 (255)	12.88 (327)
Door Opening Size - in (mm)				11 5/8 (295)	14 5/16 (364)	16 1/4 (413)	16 1/4 (413)	18 1/2 (470)
Door Bottom to Floor - in (mm)				14 3/8 (365)	14 (356)	14 9/16 (370)	14 15/16 (379)	17 15/16 (455)
Water Inlet Connection - in (mm)				2 @ 3/4 (19)	2 @ 3/4 (19)	2 @ 3/4 (19)	2 @ 3/4 (19)	2 @ 3/4 (19)
Drain Diameter - in (mm)				1 @ 2 (51)	1 @ 2 (51)	1 @ 3 (76)	1 @ 3 (76)	1 @ 3 (76)
Drain Height to Floor - in (mm)			m)	4 11/16 (119)	4 1/8 (105)	4 1/2 (115)	4 7/8 (124)	6 3/8 (163)
Motor Power Consumption - HP (kW)			- HP (kW)	1 (.75)	2 (1.5)	2 (1.5)	3 (2.2)	5 (3.7)
Total # of Speeds				6, 9	6, 9	6, 9	6, 9	6, 9
Cylinder Speeds - RPM			Gentle	37 (0.4)	34 (0.4)	33 (0.4)	31 (0.4)	28 (0.4)
(G-Force)			Wash	51 (.8)	48 (.8)	46 (.8)	43 (.8)	39 (.8)
		Distribution	92 (2.5)	86 (2.5)	82 (2.5)	77 (2.5)	70 (2.5)	
		Very Low	301 (27)	282 (27)	269 (27)	252 (27)	230 (27)	
		Low	518 (80)	485 (80)	464 (80)	434 (80)	396 (80)	
Very			Medium	579 (100)	542 (100)	518 (100)	485 (100)	443 (100)
			High	648 (120)	606 (120)	579 (120)	542 (120)	495 (120)
			Very High	710 (150)	664 (150)	635 (150)	594 (150)	542 (150)
			Ultra High	819 (200)	766 ( 200)	733 ( 200)	686 (200)	626 (200)
1	В		120/60/1	15-8	20-16	20-16	N/A	N/A
Voltage wires/ Circuit	X 200-208/2		20-240/50/60/3/1/3	15-4 (1 Ph) 15-3 (3 Ph)	15-6 (1 Ph) 15-4 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-10 (1 Ph) 15-6 (3 Ph)	15-12 (1 Ph) 15-8 (3 Ph)
Breaker - FLA	Q 200-208		/220-240/50/60/3/3	15-3	15-4	15-4	15-6	15-8
1	N		440-480/50/60/3/3	15-2	15-3	15-3	15-4	15-5
F	Р		380-415/50/60/3/3	15-2	15-3	15-3	15-4	15-5
Shipping Dimensions		nsions	Width	28 (711)	31 1/2 (800)	32 1/2 (826)	37 1/2 (953)	44 (1118)
Approx in (mm)			Depth	33 13/16 (859)	38 5/16 (973)	43 1/2 (1105)	46 15/16 (1191)	54 1/2 (1384)
			Height	49 3/8 (1256)	51 5/16 (1303)	53 5/8 (1361)	56 5/16 (1430)	58 5/8 (1488)
Net Weight - Ib (kg)				335 (152)	460 (209)	550 (249)	695 (315)	1210 (549)
Shipping Weight - Ib (kg)				365 (166)	495 (225)	590 (268)	745 (338)	1260 (572)
Slat Crate Shipping Weight - lb (kg)				450 (204)	590 (268)	690 (313)	860 (390)	1385 (628)
*Agency Approvals				cETL <sub>us</sub> , CE	cETL <sub>us</sub> , CE			



# To learn more, or to find a distributor in your area, visit UNIMAC.COM Alliance Laundry Systems - Shepard St, Ripon WI 54971 - 1.800.587.5458

 $^{\star}\,\mathrm{Agency}$  approvals may vary depending on configuration.

Consult factory for details. Contact your distributor for specific models available with CE. For electrical specifications, circuit breaker requirements and full load amperages, see your authorized UniMac® distributor. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

SERIOUS ABOUT LAUNDRY.

© 2016 Alliance Laundry Systems LLC. Printed in the U.S.A.

DISTRIBUTOR INFORMATION HERE